



	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12			
No del #	F0.4100DFD.070	F8414CDFB-	F8416CDFB-	F8418CDFB-	F8420CDFB-	F100100DED 070			
Model #	F8412CDFB-070	070	070	070	070	F10212CDFB-070			
CAPACITIES									
GVWR (lbs)		7000							
GAWR (lbs/axle)		3500							
CHASSIS									
Frame	6" x 2" Steel Tube								
Tongue		ı	6" Extension, 6" x	2" Steel Triple Tul	эе				
Crossmembers			Formed Steel	, 16" On-Center					
Integrated Step(s)						Interior Recessed			
Coupler			2-5/16"	Adjustable					
Safety Chains			DOT C	ompliant					
Tongue Jack			7K Drop Leg,	Frame Mounted					
Wall Studs			Steel Tube,	16" On-Center					
Roof Bows	Steel Tube, 8" On-Center								
Front Profile		Flat							
Stabilizers	Rear Drop-Leg Jacks								
Rear Door	Barn-Style Double with Cambar and Step Bumper								
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback								
Vents	Roof Vent Frame, Salem Sidewall Airflow								
Fenders	Aluminum Treadplate								
Axle	(2) 3500 lb. Torsion Brake								
Hubs	Easy Lube								
Breakaway		Battery, Switch, and Lanyard							
Tires		ST205/75R15C 6-PR							
Wheels		15", 5-	Hole Steel, Cente	· · ·	Rings1				
Exterior Finish				luminum					
Undercoating				motive					
Exterior Fastening				d (Screwless)					
Exterior Trim	2.7" Botton	n Extrusion, 2.7" To	-		iers, Color Matchi	ng Rear Hoop			
Stone Guard				ATP					
Roof			Flat Top Seam	nless Aluminum	r Laddar Daaka	(4) Haavy Duty Laddar			
Exterior Storage	(4) Heavy Duty L	adder Racks with F	Rear Roller	''	/ Ladder Racks ar Roller	(4) Heavy Duty Ladder Racks with Rear Roller			
<b>Exterior Accessories</b>		ATP and Eng	ineered Wood Tor	gue Cover, Front	Access Ladder				
Interior Walls			Enginee	red Wood					
Interior Lights		(	1) LED, (2) 48" 11	OV Wrap Around L	ED				
Switches			(1) 110V, (2) Pair	Top Fuel 3-Way, 12	2V				







	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	
Fixtures	(2) Tool Cabinets with Aluminum Work Station	(3) Tool Cabinets Work S		(4) Tool Cabinets Work S		(2) Tool Cabinets with Aluminum Work Station	
Cargo Control		(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row					
<b>Connector Plug</b>		Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Recept	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					







	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20				
Model #	F10214CDFB-070	F10216CDFB-070	F10218CDFB-070	F10220CDFB-070				
	1102140010-070	1 102 10001 0-070	1 102 100D1 B-070	1102200010-070				
CAPACITIES								
GVWR (lbs)			00					
GAWR (lbs/axle)	3500							
CHASSIS								
Frame	6" x 2" Steel Tube							
Tongue	6" Extension, 6" x 2" Steel Triple Tube							
Crossmembers		Formed Steel,	16" On-Center					
Integrated Step(s)		Interior F	Recessed					
Coupler		2-5/16" A	djustable					
Safety Chains		DOT Co	mpliant					
Tongue Jack		7K Drop Leg, F	rame Mounted					
Wall Studs		Steel Tube, 1	6" On-Center					
Roof Bows		Steel Tube, 8	3" On-Center					
Front Profile		Fl	at					
Stabilizers		Rear Drop-	Leg Jacks					
Rear Door		Barn-Style Double with C	ambar and Step Bumper					
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Aluminum Treadplate							
Axle	(2) 3500 lb. Torsion Brake							
lubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard							
Tires	ST205/75R15C 6-PR							
Wheels	15", 5-Hole Steel, Center Caps and Beauty Rings1							
Exterior Finish	.030" Aluminum							
Undercoating		Auton						
Exterior Fastening		VHB Bonded	•					
Exterior Trim	2.7" Bottom Extru	sion, 2.7" Top Extrusion, ATP F	·	tching Rear Hoop				
Stone Guard		24"						
Roof	(4) 11 - 5 - 1 - 1 - 1	Flat Top Seam		n I Wh n n W				
Exterior Storage	· · · · · ·	Racks with Rear Roller	, , , ,	Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Tong	•	Γ				
nterior Walls			ed Wood					
Interior Lights		, , , , ,	V Wrap Around LED					
Switches	(2) Tool Cabinatath	, , , , ,	op Fuel 3-Way, 12V	Aluminum Wark Ctation				
Fixtures	(3) Tool Cabinets with		, ,	Aluminum Work Station				
Cargo Control	(4	l) 5000 lb. Recessed D-Rings, I		W .				
Connector Plug	(0) p	Round 7-		oilliahto				
Exterior Lights	(Z) Rea	r LED Loading, Full LED, DOT C	omphant, integrated Backup/ I	anngnts				







	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior					
1104 Liecuicai		Rece	ptacles			







	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Model #	F8412CDFB-100	F8414CDFB-	F8416CDFB-	F8418CDFB-	F8420CDFB-	F10212CDFB-100		
Model #	F8412CDFB-100	100	100	100	100	F10212CDFB-100		
CAPACITIES								
GVWR (lbs)			99	900				
GAWR (lbs/axle)		5000						
CHASSIS								
Frame	6" x 2" Steel Tube							
Tongue		ı	6" Extension, 6" x	2" Steel Triple Tul	oe .			
Crossmembers			Formed Steel	, 16" On-Center				
Integrated Step(s)						Interior Recessed		
Coupler			2-5/16" /	Adjustable				
Safety Chains			DOT Co	ompliant				
Tongue Jack			7K Drop Leg,	Frame Mounted				
Wall Studs				16" On-Center				
Roof Bows		Steel Tube, 8" On-Center						
Front Profile		Flat						
Stabilizers	Rear Drop-Leg Jacks							
Rear Door	Barn-Style Double with Cambar and Step Bumper							
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Aluminum Treadplate							
Axle	(2) 5200 lb. Torsion Brake							
Hubs	Easy Lube							
Breakaway 		Battery, Switch, and Lanyard						
Tires		4=11.4		SR15D 8-PR				
Wheels		15", 6-		r Caps and Beauty · · ·	Rings1			
Exterior Finish				luminum				
Undercoating				motive				
Exterior Fastening Exterior Trim	2.7" Dottom	n Extrusion, 2.7" To		d (Screwless)	oro Color Matabi	ing Door Hoon		
Stone Guard	Z.7 BULLUII	i Extrusion, 2.7 10	•	ATP	ers, Color Matchi	під кеаг поор		
Roof				iless Aluminum				
RUUI			riat top Seati		Ladder Racks	(4) Heavy Duty Ladder		
Exterior Storage	(4) Heavy Duty La	adder Racks with F	Rear Roller		ar Roller	Racks with Rear Roller		
Exterior Accessories		ATP and Eng	ineered Wood Ton	gue Cover, Front A				
Interior Walls			Enginee	red Wood				
Interior Lights		(	1) LED, (2) 48" 11	OV Wrap Around L	ED			
Switches		(	(1) 110V, (2) Pair <sup>-</sup>	Top Fuel 3-Way, 12	2V			







	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	
Fixtures	(2) Tool Cabinets with Aluminum Work Station	(3) Tool Cabinets Work S		` '	s with Aluminum Station	(2) Tool Cabinets with Aluminum Work Station	
Cargo Control	(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row						
<b>Connector Plug</b>		Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
110v Electrical	(1) Exterior GFI Recep	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					







	8.5 x 14	8.5 x 16	8.5 x 18	0.5 ** 20				
Model #	F10214CDFB-100	8.5 x 16 F10216CDFB-100	F10218CDFB-100	8.5 x 20 F10220CDFB-100				
	F10214CDFB-100	FIUZIOCDFB-IUU	F10210CDFB-100	F10220CDFB-100				
CAPACITIES								
GVWR (lbs)		99	00					
GAWR (Ibs/axle)	5000							
CHASSIS								
Frame	6" x 2" Steel Tube							
Tongue	6" Extension, 6" x 2" Steel Triple Tube							
Crossmembers		Formed Steel,	16" On-Center					
Integrated Step(s)		Interior F	Recessed					
Coupler		2-5/16" A	djustable					
Safety Chains		DOT Co	mpliant					
Tongue Jack		7K Drop Leg, F	rame Mounted					
Wall Studs		Steel Tube, 1	6" On-Center					
Roof Bows		Steel Tube, 8	B" On-Center					
Front Profile		Fl	at					
Stabilizers		Rear Drop-	Leg Jacks					
Rear Door		Barn-Style Double with C	ambar and Step Bumper					
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Aluminum Treadplate							
Axle	(2) 5200 lb. Torsion Brake							
Hubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard							
Tires	ST225/75R15D 8-PR							
Wheels	15", 6-Hole Steel, Center Caps and Beauty Rings1							
Exterior Finish	.030" Aluminum							
Undercoating		Auton						
Exterior Fastening		VHB Bonded	•					
Exterior Trim	2.7" Bottom Extru	ısion, 2.7" Top Extrusion, ATP F	•	tching Rear Hoop				
Stone Guard		24".						
Roof	(4) 11	Flat Top Seaml		··				
Exterior Storage	· · · · ·	Racks with Rear Roller		Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Tong		r				
Interior Walls		Engineer						
Interior Lights		(1) LED, (2) 48" 110	•					
Switches	(2) Table California (4)	(1) 110V, (2) Pair T	•	Al				
Fixtures	· · · ·	Aluminum Work Station	· ,	Aluminum Work Station				
Cargo Control	(4	1) 5000 lb. Recessed D-Rings, F		W				
Connector Plug	(0) =	Round 7-		:111:L.a.				
Exterior Lights	(2) Rea	r LED Loading, Full LED, DOT Co	ompliant, integrated Backup/Ta	aiiiignts				







	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior					
1104 Liecuicai		Rece	ptacles			

