

TRIUMPH FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Model #	F10228THFBGNCH-100	F10230THFBGNCH-100	F10232THFBGNCH-100	F10234THFBGNCH-100		
CAPACITIES						
GVWR (lbs)		99	900			
GAWR (lbs/axle)		50	000			
CHASSIS						
Frame		8" x 2" S	teel Tube			
Tongue		Goos	eneck			
Crossmembers		Formed Steel	16" On-Center			
Integrated Step(s)		Interior	Recessed			
Coupler		2-5/16" (Gooseneck			
Safety Chains		DOT Co	ompliant			
Tongue Jack		Dual 12K, 2-Spe	eed Landing Gear			
Wall Studs		Steel Tube,	16" On-Center			
Roof Bows		Steel Tube,	16" On-Center			
Front Profile		F	lat			
Beavertail		4	8"			
Ramp(s)		16" Extension with Bullnos	se Cap, 4000 lb. with Assist			
Side Door		36" Wide Flush Lock, C	ast Aluminum Holdback			
Access Doors	16" x 48" in Riser					
Vents		Sidewa	II Airflow			
Fenders		Aluminum	Treadplate			
Axle		(2) 5200 lb. Dr	op Spring Brake			
Hubs		Easy	Lube			
Breakaway		Battery, Switc	h, and Lanyard			
Tires		ST225/75	R15D 8-PR			
Wheels		15", 6-Hol	e Aluminum			
Exterior Finish		.030" A	luminum			
Undercoating		Auto	motive			
Exterior Fastening		VHB Bonde	d (Screwless)			
Exterior Trim	2.7" Bottor	n Extrusion, 2.7" Top Extrusion,	ATP Riser Wall, Brite Aluminum	n Rear Hoop		
Rear Spoiler		9" Brite Alu	minum Flare			
Roof		Flat Top Seam	less Aluminum			
Interior Walls			red Wood			
Interior Trim		Extruded Aluminu	m Wall Transitions			
Ceiling		White Vinyl Liner w	ith Aluminum Coves			
Flooring		3/4" Engin	eered Wood			
Interior Lights		(2)	LED			
Switches		(1) Top Fuel Dome Light, 12\	/, (1) Top Fuel Load Light, 12V			
Cargo Control		(4) 5000 lb. Re	cessed D-Rings			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC



TRIUMPH FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Connector Plug	Round 7-pin Blade						
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights						
DIMENSIONS							
Overall Length	344"	368"	392"	416"			
Deck Length	337"	361"	385"	409"			
Deck Width	96.88"						
Deck Height	23.75"						





TRIUMPH FLAT TOP FLAT FRONT 15K

	8.5 x 36	8.5 x 38				
Model #	F10236THFBGNCH-150	F10238THFBGNCH-150				
CAPACITIES						
GVWR (lbs)	15000					
GAWR (lbs/axle)		5000				
CHASSIS						
Frame	8" x	2" Steel Tube				
Tongue	(Gooseneck				
Crossmembers	Formed S	Steel, 16" On-Center				
Integrated Step(s)	Inte	rior Recessed				
Coupler	2-5/	16" Gooseneck				
Safety Chains	DO	OT Compliant				
Tongue Jack	Dual 12K, 2	-Speed Landing Gear				
Wall Studs	Steel Tu	be, 16" On-Center				
Roof Bows	Steel Tu	be, 16" On-Center				
Front Profile		Flat				
Beavertail		48"				
Ramp(s)	16" Extension with Bu	llnose Cap, 4000 lb. with Assist				
Side Door	36" Wide Flush Loo	ck, Cast Aluminum Holdback				
Access Doors	16" x 48" in Riser					
Vents	Sid	ewall Airflow				
Fenders	Alumi	num Treadplate				
Axle	(3) 5200 li	b. Drop Spring Brake				
Hubs		Easy Lube				
Breakaway	Battery, S	Switch, and Lanyard				
Tires	ST22	5/75R15D 8-PR				
Wheels	15", 6·	-Hole Aluminum				
Exterior Finish	.03	0" Aluminum				
Undercoating	Į.	Automotive				
Exterior Fastening	VHB Bo	nded (Screwless)				
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrus	sion, ATP Riser Wall, Brite Aluminum Rear Hoop				
Rear Spoiler	9" Brite	e Aluminum Flare				
Roof	Flat Top S	Seamless Aluminum				
Interior Walls	Eng	ineered Wood				
Interior Trim	Extruded Alui	minum Wall Transitions				
Ceiling	White Vinyl Lin	er with Aluminum Coves				
Flooring	3/4" E	ngineered Wood				
Interior Lights		(2) LED				
Switches	(1) Top Fuel Dome Light	, 12V, (1) Top Fuel Load Light, 12V				
Cargo Control	(4) 5000 li	b. Recessed D-Rings				





TRIUMPH FLAT TOP FLAT FRONT 15K

	8.5 x 36	8.5 x 38			
Connector Plug	Round 7-pin Blade				
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				
DIMENSIONS					
Overall Length	440"	464"			
Deck Length	433"	457"			
Deck Width	96.88"				
Deck Height	23.	75"			





TRIUMPH FLAT TOP FLAT FRONT 21K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
	F10240THFBGNCH-	F10242THFBGNCH-	F10244THFBGNCH-	F10246THFBGNCH-	F10248THFBGNCH-	F10250THFBGNCH-
Model #	210	210	210	210	210	210
CAPACITIES						
GVWR (lbs)			21	000		
GAWR (lbs/axle)				000		
CHASSIS						
Frame			8" x 2" S	teel Tube		
Tongue			Goos	eneck		
Crossmembers			Formed Steel,	16" On-Center		
Integrated Step(s)			Interior I	Recessed		
Coupler			2-5/16" G	ooseneck		
Safety Chains			DOT Co	mpliant		
Tongue Jack			Dual 12K, 2-Spe	ed Landing Gear		
Wall Studs			Steel Tube, 1	6" On-Center		
Roof Bows			Steel Tube, 1	6" On-Center		
Front Profile			F	at		
Beavertail			4	8"		
Ramp(s)		16" E	extension with Bullnos	e Cap, 4000 lb. with A	Assist	
Side Door		30	6" Wide Flush Lock, C		ck	
Access Doors			16" x 48	" in Riser		
Vents			Sidewal	l Airflow		
Fenders				Treadplate		
Axle			• • •	op Spring Brake		
Hubs			•	Lube		
Breakaway			•	h, and Lanyard		
Tires				R16E 10-PR		
Wheels			•	Aluminum		
Exterior Finish				uminum		
Undercoating				notive		
Exterior Fastening				(Screwless)		
Exterior Trim		2.7" Bottom Extrusio	n, 2.7" Top Extrusion,		Aluminum Rear Hoop	
Rear Spoiler				minum Flare		
Roof				less Aluminum		
Interior Walls Interior Trim				red Wood m Wall Transitions		
Ceiling			•	ith Aluminum Coves		
Flooring				eered Wood LED		
Interior Lights Switches		/1\ T	` '		nh+ 12\/	
		(1) lop	Fuel Dome Light, 12V	. ,	yııı, ı∠v	
Cargo Control			* *	cessed D-Rings		
Connector Plug			Kound /-	pin Blade		



 $Specifications \ and \ Pricing \ subject \ to \ change \ without \ notice, \ please \ reference \ confirmation \ sheet \ for \ final \ pricing.$



TRIUMPH FLAT TOP FLAT FRONT 21K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50	
Exterior Lights		(1) Rear LED Loa	iding, Full LED, DOT Co	ompliant, Integrated B	ackup/Taillights		
DIMENSIONS							
Overall Length	488"	512"	536"	560"	584"	608"	
Deck Length	481"	505"	529"	553"	577"	601"	
Deck Width	96.88"						
Deck Height	25.25"						



 $Specifications \ and \ Pricing \ subject \ to \ change \ without \ notice, \ please \ reference \ confirmation \ sheet \ for \ final \ pricing.$





TRIUMPH FLAT TOP FLAT FRONT 21K

	8.5 x 52
Model #	F10252THFBGNCH-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(3) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Wheels	16", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop
Rear Spoiler	9" Brite Aluminum Flare
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Round 7-pin Blade
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



 $Specifications \ and \ Pricing \ subject \ to \ change \ without \ notice, \ please \ reference \ confirmation \ sheet \ for \ final \ pricing.$

© 2025 Novae LLC



TRIUMPH FLAT TOP FLAT FRONT 21K

	8.5 x 52
DIMENSIONS	
Overall Length	632"
Deck Length	625"
Deck Width	96.88"
Deck Height	25.25"





TRIUMPH FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	F10228THFBGNCH-160	F10230THFBGNCH-160	F10232THFBGNCH-160	F10234THFBGNCH-160			
CAPACITIES							
GVWR (lbs)		16	000				
GAWR (lbs/axle)		80	000				
CHASSIS							
Frame		8" x 2" S	teel Tube				
Tongue		Goos	eneck				
Crossmembers		Formed Steel	16" On-Center				
Integrated Step(s)		Interior	Recessed				
Coupler		2-5/16" (Gooseneck				
Safety Chains		DOT Co	ompliant				
Tongue Jack		Dual 12K, 2-Spe	eed Landing Gear				
Wall Studs		•	16" On-Center				
Roof Bows		Steel Tube,	16" On-Center				
Front Profile		F	lat				
Beavertail		4	8"				
Ramp(s)		16" Extension with Bullnos	se Cap, 4000 lb. with Assist				
Side Door		36" Wide Flush Lock, C	ast Aluminum Holdback				
Access Doors		16" x 48	" in Riser				
Vents		Sidewa	II Airflow				
Fenders		Aluminum	Treadplate				
Axle		(2) 8000 lb. Dr	op Spring Brake				
Hubs		Oil	Bath				
Breakaway		Battery, Switc	h, and Lanyard				
Tires		215/75R1	7.5J 18-PR				
Wheels		17.5", 8-Ho	le Aluminum				
Exterior Finish		.030" A	luminum				
Undercoating			motive				
Exterior Fastening			d (Screwless)				
Exterior Trim	2.7" Bottor	•	ATP Riser Wall, Brite Aluminum	n Rear Hoop			
Rear Spoiler			minum Flare				
Roof		•	lless Aluminum				
Interior Walls			red Wood				
Interior Trim			m Wall Transitions				
Ceiling		•	ith Aluminum Coves				
Flooring		3/4" Engineered Wood					
Interior Lights		, ,	LED				
Switches			/, (1) Top Fuel Load Light, 12V				
Cargo Control		(4) 5000 lb. Re	cessed D-Rings				





TRIUMPH FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Connector Plug	Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					





TRIUMPH FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	F10228THFBGNCH-140	F10230THFBGNCH-140	F10232THFBGNCH-140	F10234THFBGNCH-140			
CAPACITIES							
GVWR (lbs)		14	000				
GAWR (lbs/axle)		70	000				
CHASSIS							
Frame		8" x 2" S	teel Tube				
Tongue		Goos	eneck				
Crossmembers		Formed Steel	16" On-Center				
Integrated Step(s)		Interior	Recessed				
Coupler		2-5/16" (Gooseneck				
Safety Chains		DOT Co	ompliant				
Tongue Jack		Dual 12K, 2-Spe	eed Landing Gear				
Wall Studs		Steel Tube,	16" On-Center				
Roof Bows		Steel Tube, 1	16" On-Center				
Front Profile		F	lat				
Beavertail		4	8"				
Ramp(s)		16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door		36" Wide Flush Lock, C	ast Aluminum Holdback				
Access Doors	16" x 48" in Riser						
Vents		Sidewa	II Airflow				
Fenders		Aluminum	Treadplate				
Axle		(2) 7000 lb. Dr	op Spring Brake				
Hubs		Easy	Lube				
Breakaway		Battery, Switc	h, and Lanyard				
Tires		ST235/80	R16E 10-PR				
Wheels		16", 8-Hol	e Aluminum				
Exterior Finish		.030" A	luminum				
Undercoating		Auto	motive				
Exterior Fastening		VHB Bonder	d (Screwless)				
Exterior Trim	2.7" Bottor	•	ATP Riser Wall, Brite Aluminun	n Rear Hoop			
Rear Spoiler			minum Flare				
Roof		•	lless Aluminum				
Interior Walls			red Wood				
Interior Trim			m Wall Transitions				
Ceiling		•	ith Aluminum Coves				
Flooring		•	eered Wood				
Interior Lights		· ,	LED				
Switches			/, (1) Top Fuel Load Light, 12V				
Cargo Control		(4) 5000 lb. Re	cessed D-Rings				





TRIUMPH FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Connector Plug	Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

