



	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50	
	F10240THFBGN-	F10242THFBGN-	F10244THFBGN-	F10246THFBGN-	F10248THFBGN-	F10250THFBGN-	
Model #	210	210	210	210	210	210	
CAPACITIES							
GVWR (lbs)			21	000			
GAWR (lbs/axle)			70	00			
CHASSIS							
Frame			8" x 2" S	teel Tube			
Tongue			Goos	eneck			
Crossmembers			Formed Steel,	16" On-Center			
Integrated Step(s)			Interior I	Recessed			
Coupler			2-5/16" @	ooseneck			
Safety Chains			DOT Co	mpliant			
Tongue Jack			Dual 12K, 2-Spe	ed Landing Gear			
Wall Studs			Steel Tube, 1	6" On-Center			
Roof Bows			Steel Tube, 1	6" On-Center			
Front Profile			F	at			
Ramp(s)		12" E	xtension with Bullnos	e Cap, 4000 lb. with	Assist		
Side Door		36	o" Wide Flush Lock, C	ast Aluminum Holdba	ack		
Access Doors		16" x 48" in Riser					
Vents	Sidewall Airflow						
Fenders	Aluminum Treadplate						
Axle	(3) 7000 lb. Drop Spring Brake						
Hubs			Easy	Lube			
Breakaway			Battery, Switc	h, and Lanyard			
Wheels		16", 8-Hole Aluminum					
Exterior Finish			.030" A	uminum			
Undercoating			Autor	notive			
Exterior Fastening			VHB Bonded	l (Screwless)			
Exterior Trim	2	2.7" Bottom Extrusion	n, 2.7" Top Extrusion,	ATP Riser Wall, Brite	Aluminum Rear Hoo	р	
Roof			Flat Top Seam	less Aluminum			
Interior Walls			Enginee	ed Wood			
Interior Trim	Extruded Aluminum Wall Transitions						
Ceiling	White Vinyl Liner with Aluminum Coves						
Flooring	3/4" Engineered Wood						
Interior Lights			, ,	LED			
Switches			• • •	Light, 12V			
Connector Plug				pin Blade			
Exterior Lights		Full L	ED, DOT Compliant, I	ntegrated Backup/Tai	llights		
DIMENSIONS							







	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Overall Length	488"	512"	536"	560"	584"	608"
Deck Length	481"	505"	529"	553"	577"	601"
Deck Width	96.88"					
Deck Height	25.25"					







	8.5 x 52
Model #	F10252THFBGN-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(3) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Wheels	16", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights Switches	(2) LED
Connector Plug	(1) Dome Light, 12V Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights
	run LED, DOT Gomphant, integrateu backup/ fannynts
DIMENSIONS	
Overall Length	632"







	8.5 x 52
Deck Length	625"
Deck Width	96.88"
Deck Height	25.25"







	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	F10228THFBGN-140	F10230THFBGN-140	F10232THFBGN-140	F10234THFBGN-140			
CAPACITIES							
GVWR (lbs)	14000						
GAWR (lbs/axle)		70	00				
CHASSIS							
Frame		8" x 2" Si	teel Tube				
Tongue		Goos	eneck				
Crossmembers		Formed Steel,	16" On-Center				
Integrated Step(s)		Interior F	Recessed				
Coupler		2-5/16" G	ooseneck				
Safety Chains		DOT Co	mpliant				
Tongue Jack		Dual 12K, 2-Spe	ed Landing Gear				
Wall Studs		Steel Tube, 1	6" On-Center				
Roof Bows		Steel Tube, 1	6" On-Center				
Front Profile		Fl	at				
Ramp(s)		12" Extension with Bullnos	e Cap, 4000 lb. with Assist				
Side Door		36" Wide Flush Lock, Ca	ast Aluminum Holdback				
Access Doors	16" x 48" in Riser						
/ents	Sidewall Airflow						
enders		Aluminum	Treadplate				
Axle	(2) 7000 lb. Drop Spring Brake						
lubs		•	Lube				
Breakaway	Battery, Switch, and Lanyard						
Vheels		•	Aluminum				
Exterior Finish		.030" AI	uminum				
Jndercoating			notive				
Exterior Fastening			(Screwless)				
Exterior Trim	2.7" Botton	n Extrusion, 2.7" Top Extrusion,		n Rear Hoop			
Roof		•	less Aluminum				
nterior Walls			red Wood				
nterior Trim	Extruded Aluminum Wall Transitions						
Ceiling	White Vinyl Liner with Aluminum Coves						
Flooring	3/4" Engineered Wood						
nterior Lights	(2) LED						
Switches			Light, 12V				
Connector Plug			pin Blade				
Exterior Lights		Full LED, DOT Compliant, In	ntegrated Backup/Taillights				







	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	F10228THFBGN-160	F10230THFBGN-160	F10232THFBGN-160	F10234THFBGN-160			
CAPACITIES							
GVWR (lbs)	16000						
GAWR (lbs/axle)		80	00				
CHASSIS							
Frame		8" x 2" Si	teel Tube				
Tongue		Goos	eneck				
Crossmembers		Formed Steel,	16" On-Center				
Integrated Step(s)		Interior F	Recessed				
Coupler		2-5/16" G	ooseneck				
Safety Chains		DOT Co	mpliant				
Tongue Jack		Dual 12K, 2-Spe	ed Landing Gear				
Wall Studs		Steel Tube, 1	6" On-Center				
Roof Bows		Steel Tube, 1	6" On-Center				
Front Profile		FI	at				
Ramp(s)		12" Extension with Bullnos	e Cap, 4000 lb. with Assist				
Side Door		36" Wide Flush Lock, Ca	ast Aluminum Holdback				
Access Doors	16" x 48" in Riser						
/ents	Sidewall Airflow						
enders		Aluminum	Treadplate				
Axle		(2) 8000 lb. Dro	op Spring Brake				
lubs		Oil I	Bath				
Breakaway		Battery, Switch	h, and Lanyard				
Wheels		17.5", 8-Hol	e Aluminum				
Exterior Finish		.030" AI	uminum				
Undercoating		Auton	notive				
Exterior Fastening		VHB Bonded	•				
Exterior Trim	2.7" Botton	n Extrusion, 2.7" Top Extrusion,		n Rear Hoop			
Roof		•	less Aluminum				
Interior Walls			ed Wood				
Interior Trim	Extruded Aluminum Wall Transitions						
Ceiling	White Vinyl Liner with Aluminum Coves						
Flooring	3/4" Engineered Wood						
Interior Lights	(2) LED						
Switches	(1) Dome Light, 12V						
Connector Plug			pin Blade				
Exterior Lights		Full LED, DOT Compliant, In	ntegrated Backup/Taillights				







	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	F10228THFBGN-100	F10230THFBGN-100	F10232THFBGN-100	F10234THFBGN-100			
CAPACITIES							
GVWR (lbs)		9900					
GAWR (lbs/axle)		50	000				
CHASSIS							
Frame		8" x 2" S	teel Tube				
Tongue		Goos	eneck				
Crossmembers		Formed Steel,	16" On-Center				
Integrated Step(s)		Interior I	Recessed				
Coupler		2-5/16" G	ooseneck				
Safety Chains		DOT Co	mpliant				
Tongue Jack		Dual 12K, 2-Spe	ed Landing Gear				
Wall Studs		Steel Tube, 1	6" On-Center				
Roof Bows		Steel Tube, 1	6" On-Center				
Front Profile		F	at				
Ramp(s)		12" Extension with Bullnos	e Cap, 4000 lb. with Assist				
Side Door		36" Wide Flush Lock, C	ast Aluminum Holdback				
Access Doors		16" x 48	" in Riser				
Vents		Sidewall Airflow					
Fenders		Aluminum	Treadplate				
Axle		(2) 5200 lb. Dro	op Spring Brake				
Hubs		Easy	Lube				
Breakaway		Battery, Switch, and Lanyard					
Wheels		15", 6-Hole Aluminum					
Exterior Finish		.030" A	luminum				
Undercoating		Autor	notive				
Exterior Fastening		VHB Bonded	l (Screwless)				
Exterior Trim	2.7" Bottom	Extrusion, 2.7" Top Extrusion,	ATP Riser Wall, Brite Aluminun	n Rear Hoop			
Roof		Flat Top Seam	less Aluminum				
Interior Walls		Engineered Wood					
Interior Trim			m Wall Transitions				
Ceiling		•	ith Aluminum Coves				
Flooring		3/4" Engineered Wood					
Interior Lights		(2) LED					
Switches		(1) Dome Light, 12V					
Connector Plug		Round 7-pin Blade					
Exterior Lights		Full LED, DOT Compliant, In	ntegrated Backup/Taillights				
DIMENSIONS							
Overall Length	344"	368"	392"	416"			







	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34	
Deck Length	337"	361"	385"	409"	
Deck Width	96.88"				
Deck Height		23	.75"		







	8.5 x 36	8.5 x 38				
Model #	F10236THFBGN-150	F10238THFBGN-150				
CAPACITIES						
GVWR (lbs)	150	000				
GAWR (lbs/axle)	50	000				
CHASSIS						
Frame	8" x 2" S	teel Tube				
Tongue	Goos	eneck				
Crossmembers	Formed Steel,	16" On-Center				
Integrated Step(s)	Interior F	Recessed				
Coupler	2-5/16" G	Gooseneck				
Safety Chains	DOT Co	ompliant				
Tongue Jack	Dual 12K, 2-Spe	ed Landing Gear				
Wall Studs	Steel Tube, 1	6" On-Center				
Roof Bows	Steel Tube, 1	6" On-Center				
Front Profile	Fl	lat				
Ramp(s)	12" Extension with Bullnos	se Cap, 4000 lb. with Assist				
Side Door	36" Wide Flush Lock, C	ast Aluminum Holdback				
Access Doors	16" x 48	" in Riser				
Vents	Sidewal	Sidewall Airflow				
Fenders	Aluminum	Aluminum Treadplate				
Axle	(3) 5200 lb. Dro	(3) 5200 lb. Drop Spring Brake				
Hubs	Easy	Lube				
Breakaway	Battery, Switc	h, and Lanyard				
Wheels	15", 6-Hole	e Aluminum				
Exterior Finish	.030" Al	luminum				
Undercoating	Autor	motive				
Exterior Fastening	VHB Bonded	d (Screwless)				
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion,	ATP Riser Wall, Brite Aluminum Rear Hoop				
Roof	•	less Aluminum				
Interior Walls	<u> </u>	red Wood				
Interior Trim		m Wall Transitions				
Ceiling	•	White Vinyl Liner with Aluminum Coves				
Flooring	•	3/4" Engineered Wood				
Interior Lights	• • • • • • • • • • • • • • • • • • • •	(2) LED				
Switches	• • • • • • • • • • • • • • • • • • • •	(1) Dome Light, 12V				
Connector Plug		Round 7-pin Blade				
Exterior Lights	Full LED, DOT Compliant, Ir	ntegrated Backup/Taillights				
DIMENSIONS						
Overall Length	440"	464"				







	8.5 x 36	8.5 x 38
Deck Length	433"	457"
Deck Width	96.88"	
Deck Height	23.	75"







	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50	
88 - 3 - 1 //	F10240THFBGN-	F10242THFBGN-	F10244THFBGN-	F10246THFBGN-	F10248THFBGN-	F10250THFBGN-	
Model #	240	240	240	240	240	240	
CAPACITIES							
GVWR (lbs)			24	000			
GAWR (lbs/axle)			80	00			
CHASSIS							
Frame			8" x 2" S	teel Tube			
Tongue			Goos	eneck			
Crossmembers			Formed Steel,	16" On-Center			
Integrated Step(s)			Interior I	Recessed			
Coupler			2-5/16" 0	ooseneck			
Safety Chains			DOT Co	mpliant			
Tongue Jack			Dual 12K, 2-Spe	ed Landing Gear			
Wall Studs			Steel Tube, 1	6" On-Center			
Roof Bows			Steel Tube, 1	6" On-Center			
Front Profile			F	at			
Ramp(s)		12" E	xtension with Bullnos	e Cap, 4000 lb. with	Assist		
Side Door		36	b" Wide Flush Lock, C	ast Aluminum Holdba	ack		
Access Doors			16" x 48	" in Riser			
Vents	Sidewall Airflow						
Fenders		Aluminum Treadplate					
Axle			• •	op Spring Brake			
Hubs				Bath			
Breakaway			•	h, and Lanyard			
Wheels			•	e Aluminum			
Exterior Finish				uminum			
Undercoating				notive			
Exterior Fastening				l (Screwless)			
Exterior Trim	2	2.7" Bottom Extrusion	n, 2.7" Top Extrusion,	·	Aluminum Rear Hoo	p	
Roof			•	less Aluminum			
Interior Walls				ed Wood			
Interior Trim	Extruded Aluminum Wall Transitions White Vinyl Liner with Aluminum Coves						
Ceiling Flooring			•	eered Wood			
				LED			
Interior Lights Switches			, ,	Light, 12V			
			• • •	pin Blade			
Connector Plug		Coll 1	- , Round ED, DOT Compliant, Ii	•	lliahte		
Exterior Lights		Full L	בט, טטו Gomphant, II	пеугатей васкир/ Гаг	mynts		







	8.5 x 52
Model #	F10252THFBGN-240
CAPACITIES	
GVWR (lbs)	24000
GAWR (lbs/axle)	8000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(3) 8000 lb. Drop Spring Brake
Hubs	Oil Bath
Breakaway	Battery, Switch, and Lanyard
Wheels	17.5", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights

